

What is claimed is:

1. An apparatus for trans-coding between code excited linear prediction (CELP) type codecs having different
5 bandwidths, comprising:

a formant parameter translating means for translating formant parameters from input CELP format to output CELP format and generating formant parameters in an output CELP format;

10 a formant parameter quantizing means for receiving the translated formant parameters and quantizing the translated formant parameters;

an excitation parameter translating means for translating excitation parameters from input CELP format to output CELP
15 format and generating excitation parameters in an output CELP format; and

an excitation quantizing means for receiving the translated excitation parameters and quantizing the translated excitation parameters.

20

2. The apparatus as recited in claim 1, wherein the formant parameter translating means includes:

a first type converting means for receiving formant parameters from the input bit stream and converting formant
25 parameters from the type specified in the input CELP format to a suitable type for formant bandwidth conversion;

a formant bandwidth converting means for receiving the

input formant parameters from the first type converting means and converting the formant parameters from a bandwidth of an input CELP format to a bandwidth of an output CELP format;

5 a second type converting means for receiving the bandwidth-corrected formant parameters from the formant bandwidth converting means and converting the formant parameters from the type used in the formant bandwidth converting means to a suitable type for model order conversion;

10 a formant model order converting means for receiving the input formant parameters from the second type converting means and converting the formant parameters from the model order in the input CELP format into the model order in the output CELP format;

15 a third type converting means for receiving the order-corrected formant parameters from the formant model order converting means and converting the formant parameters from the type used in the model order converting means to a suitable type for frame rate conversion;

20 a formant frame rate converting means for receiving the input formant parameters from the third type converting means and converting the formant parameters from the frame rate in the input CELP format to the frame rate in the output CELP format; and

25 a forth type converting means for receiving the frame rate-corrected formant parameters from the formant frame rate converting means and converting the formant parameters from

the type used in the formant frame rate converting means to a suitable type for the formant parameter quantizing means in the output CELP format.

5 3. The apparatus as recited in claim 2, wherein the formant bandwidth converting means compresses the bandwidth of the formant parameters and generates the bandwidth-corrected formant parameters when the bandwidth of the input CELP format is wider than that of the output CELP format and expands the
10 bandwidth of the formant parameters and generates the bandwidth-corrected formant parameters when the bandwidth of the input CELP format is narrower than that of the output CELP format.

15 4. The apparatus as recited in claim 2, wherein the formant model order converting means truncates the bandwidth-corrected formant parameters and generates the model order-corrected formant parameters when the model order of the bandwidth-corrected formant parameters is higher than that of
20 the output CELP format and extends the bandwidth-corrected formant parameters and generates model order-corrected formant parameters when the model order of the bandwidth-corrected formant parameters is lower than that of the output CELP format.

25

 5. The apparatus as recited in claim 2, wherein the formant frame rate converting means decimates the order-

corrected formant filter coefficients and generates the frame rate-corrected formant parameters when the frame rate of the order-corrected formant parameters is higher than that of the output CELP format and interpolates the order-corrected formant parameters and generates the frame rate-corrected formant parameters when the frame rate of the order-corrected formant parameters is lower than that of the output CELP format.

10 6. The apparatus as recited in claim 1, wherein the excitation parameter translating means includes:

 an excitation synthesizing means for generating an excitation signal by using input CELP format excitation parameters;

15 an excitation bandwidth converting means for receiving the synthesized excitation signal from the excitation synthesizing means and converting the excitation signal from the bandwidth of the input CELP format to the bandwidth of the output CELP format;

20 a fifth type converting means for receiving the frame rate-corrected formant parameters from the formant frame rate converting means and converting the frame rate-corrected formant parameters from the type used in the frame rate converting means to a suitable type for formant coefficient interpolation;

25 a formant coefficient interpolating means for receiving the formant filter coefficients from the fifth type converting

means and generating the each formant filter coefficients set for sub-frame analysis;

5 a sixth type converting means for receiving the formant filter coefficients of each sub-frame from the formant coefficient interpolating means and converting the formant filter coefficients of each sub-frame from the type used in the formant coefficient interpolating means to a suitable type for perceptual weighting filtering;

10 a perceptual weighting filtering means for receiving the formant filter coefficients from the sixth type converting means and constructs a corresponding perceptual weighting filter, then receiving the excitation signal corresponding to each sub-frame from the excitation bandwidth converting means, and performing filtering the excitation signal through the
15 constructed perceptual weighting filter;

an adaptive codebook searching means for finding optimal pitch delay in the output CELP format for each sub-frame generally based on the conventional analysis-by-synthesis scheme using an adaptive codebook target signal, which is the
20 output signal of the perceptual weighting filtering means and then computing a accompanying gain of the adaptive codebook; and

a fixed codebook searching means for finding the best model for the residual signal from the pre-defined codebook in
25 the output CELP format for each sub-frame generally based on the conventional analysis-by-synthesis scheme using a signal produced by subtracting the contribution of the adaptive

codebook from the adaptive codebook target signal and then computing an accompanying gain of the fixed codebook.

7. The apparatus as recited in claim 6, wherein the
5 excitation bandwidth converting means decimates the
synthesized excitation signal from a sampling frequency of
input CELP format to that of output CELP format and generates
the bandwidth-converted excitation signal when a bandwidth of
the input CELP format is wider than that of the output CELP
10 forma, and interpolates the synthesized excitation signal from
a sampling frequency of input CELP format to that of output
CELP format and generates the bandwidth-converted excitation
signal when the bandwidth of the input CELP format is narrower
than that of the output CELP format.

15

8. A method for trans-coding between CELP type codecs
having different bandwidths, comprising the steps of:

a) translating formant parameters from input CELP format
to output CELP format and generating formant parameters in an
20 output CELP format;

b) receiving the translated formant parameters and
quantizing the translated formant parameters;

c) translating excitation parameters from input CELP
format to output CELP format and generating excitation
25 parameters in an output CELP format; and

d) receiving the translated excitation parameters and
quantizing the translated excitation parameters.

9. A computer readable recording medium for executing a method of trans-coding between CELP type codecs having different bandwidths, comprising the functions of:

5 a) translating formant parameters from input CELP format to output CELP format and generating formant parameters in an output CELP format;

b) receiving the translated formant parameters and quantizing the translated formant parameters;

10 c) translating excitation parameters from input CELP format to output CELP format and generating excitation parameters in an output CELP format; and

d) receiving the translated excitation parameters and quantizing the translated excitation parameters.